

## PS3107-S7 1.8 SATA SSD

## (Reference Design)

Phison's PS3107 1.8" SATA SSD delivers all the advantages of flash disk technology with the Serial ATA I/II interface and is fully compliant with the standard 1.8-inch form factor and provides hot-swapping when removing/replacing/upgrading flash disks as well. PS3107 1.8" SATA SSD contributes extensive advantages over the traditional Hard Drive Disk (HDD). Promising a wide range of capacity, high read/write performance, as well as low power consumption, PS3107 1.8" SATA SSD is the ideal storage solution which satisfies major market demands of various applications.



## **Product Specification**

| Capacity              | 4GB ~ 256GB   |
|-----------------------|---|
| SATA Interface        | SATA Revision 2.6   |
|                       | SATA 1.5Gbps and 3Gbps interface                              |
| Flash Interface       | Flash Type: SLC, MLC  |
|                       | 1pcs to 8pcs of TSOP flash                                    |
|                       | 1pcs to 4pcs of BGA flash                                     |
| Performance*          | Read: up to 135 MB/s  |
|                       | Write: up to 90 MB/s  |
| Power Consumption*    | Active mode: < 1570 mW  |
|                       | Idle mode: < 100 mW   |
| MTBF                  | More than 1,000,000 hours                                     |
| Advanced Flash        | Static and Dynamic Wear Leveling, Bad Block Management, TRIM, |
| Management            | SMART, Over-Provision, Firmware Update                        |
| Operating Voltage     | 3.3V (default); 5V (optional)                                 |
| Operating Temperature | 0°C ~ 70°C  |
| Storage Temperature   | -40°C ~ 85°C  |
| *- ·                  |   |

<sup>\*</sup> Performance and Power Consumption may differ according to flash type, flash configuration, SDR configuration, and platform.

Phison Electronics Corp.
TEL: +886-37-586-896
FAX: +886-37-587-868
E-mail: sales@phison.com/
support@phison.com