



World's First PCIe Gen 5 Mainstream SSD

Phison E31T is the world's-first DRAM-less PCIe Gen5 SSD controller IC solution that pushes for true PCIe Gen5 bandwidth above 10GB/s while taking cost-centric SSD performance to new heights. On top of its refined power efficiency and advanced cost-effective DRAM-less design, Phison E31T practically eliminates the need to choose between high-performance and affordable pricing for PC builders and consumers.



Application

High-performance PCs and workstations
Gaming PCs/gaming consoles

Product Features

Market-leading Performance

Manufactured using TSMC's 7nm process technology, the E31T is optimized for a PCIe Gen5x4 interface, enabling SSDs with maximized bandwidths and link efficiency. Paired with state-of-the-art 3D NAND flash memory chips, the PS5031-E31T handles application payloads immaculately with minimal latency.

Superb Power Efficiency

Through its DRAM-less configuration and a range of design enhancements, the E31T offers a tremendous reduction in power consumption compared to DRAM-equipped solutions. With advanced power management measures such as support of the L1.2 low power state, E31T is able to effectively help motherboards with power reduction during idle periods.

Outstanding Cost-effectiveness

As a cutting-edge DRAM-less solution, the E31T not only saturates the PCIe Gen5 interface bandwidth as well as any DRAM-boosted solution does, but it does so while retaining compelling cost-savings, creating invaluable design-in opportunities in cost-sensitive consumer markets.

Phison 7th Generation LDPC ECC Engine

Phison's proprietary seventh-generation ECC engine based on the LDPC coding scheme effectively maintains NAND flash data reliability. Relative to the prior generation, the 7th Gen engine is added with multiple advanced features for increased performance and flexibility to accommodate state-of-the-art NAND flash memory devices.

CONTROLLER

PS5031-E31T

Features	Specifications
Host Interface	<ul style="list-style-type: none">- PCIe 5.0 x4 (Bandwidth: 32GT/s x4)- Backward compatible with existing PCIe generation transfer rates- Compliance with PCI Express Base Specification Revision 5.0- Compliance with NVMe 2.0- Host Memory Buffer (HMB) support
Processor	<ul style="list-style-type: none">- Single-CPU architecture with built-in 32-bit microcontroller- TSMC 7nm process technology
Flash Controller	<ul style="list-style-type: none">- Up to 4 Channels with 16 chip enable (CE) counts- Flash transfer rate up to 3600MT/s- Capacity up to 8TB- Support 3D TLC and QLC NAND flash memory- Compliance with Toggle 5.1 and ONFi 5.1- Flash I/O operating voltage supply 1.2V
Data Reliability	<ul style="list-style-type: none">- Phison 7th generation LDPC ECC & RAID ECC engine- End-To-End Data Path Protection
Security	<ul style="list-style-type: none">- AES256- SHA384- SHA512- RSA4096- TCG OPAL 2.01- Pyrite 2.01
Performance	<ul style="list-style-type: none">- Sequential Read up to 10,600 MB/s- Sequential Write up to 9,600 MB/s- 4K Random Read up to 1,500K IOPS- 4K Random Write up to 2,200K IOPS
Power Management	<ul style="list-style-type: none">- ASPM + APST Supported
Temperature Range	<ul style="list-style-type: none">- Operating range: 0~70 °C- Storage range: -40~85 °C
Package	<ul style="list-style-type: none">- 228-ball FCCSP, 8.0mm x 12.5mm
Peripheral	<ul style="list-style-type: none">- Built-in internal thermal sensor- GPIO pins- Built-in UART function- I3C, I2C and SPI for external ROM- Support of SMBus



THE DATA WITHIN THIS SPECIFICATION IS SUBJECT TO CHANGE BY PHISON WITHOUT NOTICE. PERFORMANCE NUMBERS MAY VARY BASED ON SYSTEM CONFIGURATION AND TESTING CONDITIONS.

COPYRIGHT © 2024 PHISON ELECTRONICS, ALL RIGHTS RESERVED.

Find more information and resources at: phisonblog.com and phison.com